


Two Electrode Gas Tube Surge Arrester

Part Number: Y08SV-272B



Features:


- UL 1449 & UL1414 Recognized
(File E328370 & E165829)
- 100% Lead-Free (RoHS Compliant)
- IEC60950 Line Isolation
- 3.1 mm Internal Electrode Gap
(Meets VDE Gap Requirement)
- ISO 9001 Certified



Applications:

- Transient Voltage Surge Suppression (TVSS)
- AC Line Input Protection
- Power Supplies
- CATV Systems
- Antennas
- Test Equipment
- Set-top Boxes

Marking Example: Part Number Y08SV-272B



Electrical Characteristics

1.	DC Breakdown Voltage	5 kV/sec	2430 - 3000V		
2.	Impulse Breakdown Voltage	1 kV/μsec	< 3900V		
3.	Insulation Resistance	DC 1000V	> 10,000 M-ohm		
4.	Capacitance	1 MHz	< 1.0 pF		
5.	Impulse Discharge Current	8/20 μsec	10 kA	1 Time	
		8/20 μsec	3 kA	Each Polarity 10 Times	3 Min. Intervals
6.	Impulse Life	8/20 μsec 100A	> 300 times	1-2 Minute Intervals	

After Life Tests

7.	DC Breakdown Voltage	5 kV/sec	2230 - 3170V		
8.	Impulse Breakdown Voltage	1 kV/μsec	< 4200V		
9.	Insulation Resistance	DC 1000V	> 1 M-ohm		

SANKOSHA

SANKOSHA